

CCEWOOL® Rock Wool Pipe

Description:

CCEWOOL heat-resistance Rock Wool Pipe is made of rock wool fiber rolled by amold and cured under high temperature. For easy installation, it can be cut along the axis of the shell to facilitate construction. It ensures the tight coupling between the shell and the pipelines that needs insulation. The outer surface of the shell can be polished according to the requirement of customers to achieve the exact thickness of the insulation. Water repellent type and low chlorine type of products can be manufactured according to the requirement of customers. Aluminum foil, fiberglass cloth, and other veneer materials can also be overlaid to the surface of products.

CCEWOOL water-resistance Rock Wool Pipe is especially suitable for energy saving of hot and cold pipelines, and plays an important role in maintaining temperature, protecting personal safety, preventing condensation, and reducing noise. This product is rolled with a mold, closely coupled with pipes, and the outer surface is polished to achieve the precise insulation thickness.

Technical data and Size:

CCEWOOL® Rock Wool Pipe	
Density	120kg/m ³ (GB/T 5480.3)
Nominal diameter (Regular size)	22-612(½ "-24") mm (GB/T 5480.3)

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com

Thickness range	30-150mm (GB/T 5480.3)
Length	1000mm (GB/T 5480.3)
Thermal Conductivity*	The result is based on the test of rock wool shell 120kg/m ³ , in line with relevant test regulations. (GB/T 10294,GB/T 10296)
70℃	0.040W/ (m.K)
100℃	0.044W/ (m.K)
150℃	0.049W/ (m.K)
200℃	0.054W/ (m.K)
250℃	0.066W/ (m.K)
300℃	0.069W/ (m.K)
350℃	0.078W/ (m.K)
400℃	0.088W/ (m.K)
Maximum temperature in use	750℃ (GB/T 17430, GB50264)
Recommended temperature* in use	650℃ (ASTM C411-05, ASTM C447-03, GB50264)
Flame spread indicator	0 (ASTM E84-10)
Flue gas development index	≤25 (ASTM E84-10)
Combustion performance	A1 级 (GB 8624, EN13501-1, BS 476 Part4) A1 Level
Mass moisture absorption rate	≤1% (ASTM C1104/1104M)
Volumetric moisture absorption rate	≤1% (ASTM C1104/1104M)
Chloride content*	≤10ppm (GB/T 17393, ASTM C871-08)
Water repellency rate	99.5% (GB/T 10299)
Fiber diameter	≤6μm (GB/T 5480)

Raw Materials

Selection of high-quality natural rock made of basalt.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com

Select high-quality ores with advanced mining equipment to avoid the entry of impurities and ensure the sustainability of rock wool.

Production Process

Completely melt the raw materials under 1500°C.

Melt the raw materials at a high temperature of about 1500°C in the cupola and reduce the content of slag balls to keep the low thermal conductivity at high temperatures.

Using four-roller high speed spinner to produce fibers, greatly reduced shot content.

The fibers formed by a four-roll centrifuge at a high speed have the softening point of 900-1000°C. The special formula and mature production technology greatly reduce the content of slag balls, leading to no change in long-term use at 650°C and the enhancement of resistance to high temperatures.

Quality Control

Each shipment has a dedicated quality inspector, and a test report is provided prior to the departure of products from the factory to ensure the export quality of each shipment of CCEWOOL.

A third-party inspection (such as SGS, BV, etc.) is accepted.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com

Production is strictly in accordance with ISO9000 quality management system certification.

Products are weighed before packaging to ensure that the actual weight of a single roll is greater than the theoretical weight.

The products are packaged with puncture-resistance shrinkable film by an automatic shrink-packaging machine, suitable for long-distance transportation.

Application Performance

1. More fireproof: Class A1 fireproof insulation material, long-lasting working temperature up to 650°C
2. More environmental: neutral PH value, can be used for planting vegetables and flowers, no corrosion to heat preservation medium, and more environmental
3. No water absorption: water repellency rate as high as 99%
4. High strength: pure basalt rock wool boards with greater strengths
5. No delamination: The cotton yarn adopts a folding process and has better drawing results in experiments.
6. Various sizes with the thickness range from 30-120mm can be produced according to customers' requirements.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com