

CCEWOOL® Soluble Fiber **- CCEWOOL® Soluble Fiber Tape**

CCEWOOL® Soluble Fiber

CCEWOOL® soluble fiber is made from alkaline earth silicate fiber, including soluble blanket, board, paper, yarn, cloth, tape and rope. Soluble fiber is a body soluble fiber and can be absorbed, the color is bluish, is a new type eco-friendly insulation material. Temperature degree: 1200°C.

CCEWOOL® Soluble Fiber Tape

Description:

CCEWOOL® Soluble Fiber Tape is woven tape-shape high temperature products composed of superior soluble fibers, suitable for 1000C high temperature application. Each soluble yarn is reinforced with glass filament or inconel wire. A few binders will be burnt in a low temperature, thus it won't affect the insulation effect.

Technical data and Size:

CCEWOOL® Soluble Fiber Tape	
Thickness	1.6-6mm
Width	13-300mm

Zibo Double Egret Thermal Insulation Co.,Ltd
Add: No.105 Liuquan Rd Zibo Shandong
Tel: +86-533-7986860
Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com
Website: www.ceramicfibres.com
www.ceramicfiber.com
www.cerockwool.com

Standard Length	30m
Color	Bluish
Temperature	1100-1300℃

Raw Materials

CCEWOOL soluble fiber tape is woven from high-quality soluble fiber textile cotton.

Because of the supplements of MgO, CaO and other ingredients, CCEWOOL soluble fiber cotton can expand its viscosity range of fiber formation, enhance its fiber formation conditions, improve fiber formation rate and fiber flexibility, and reduce the content of slag balls, so, the slag ball content of CCEWOOL soluble fiber tape produced is lower than 8%. The content of the slag ball is an important index that determines the thermal conductivity of the fiber, so CCEWOOL soluble fiber tape has low thermal conductivity and excellent thermal insulation performance.

Controlling the impurity content of raw materials is an important step to ensure the heat resistance of ceramic fibers. The high impurity content will cause the coarsening of crystal grains and the increase of linear shrinkage, which is an important factor attributing to the deterioration of fiber performance and the reduction of service life.

Through strict control at every step, we reduced the impurity content of raw materials to less than 1%. The thermal shrinkage rate of CCEWOOL soluble fiber tape is lower than 3% at 1230 ℃, and they have stable quality and longer service life.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com

Production Process

The kind of organic fiber determines the flexibility of soluble fiber belts. CCEWOOL soluble fiber belts adopt organic fiber viscose with less than 15% loss on ignition and stronger flexibility.

The thickness of glass determines the strength, and the material of steel wires determines the corrosion resistance. CCEWOOL adds different reinforcing materials, such as glass fiber and heat-resistant alloy wires to ensure the quality of the ceramic fiber belts according to different operating temperatures and conditions.

The outer layer of CCEWOOL soluble fiber belts can be coated with PTFE, silica gel, vermiculite, graphite and other materials as heat insulation coating to improve their tensile strengths, erosion resistance, and abrasion resistance.

Quality Control

Each shipment has a dedicated quality inspector, and a test report is provided prior to the departure of products from the factory to ensure the export quality of each shipment of CCEWOOL.

A third-party inspection (such as SGS, BV, etc.) is accepted.

Production is strictly in accordance with ISO9000 quality management system certification.

Products are weighed before packaging to ensure that the actual weight of a single roll is greater than the theoretical weight.

The outer packaging of each carton is made of five layers of kraft paper, and the inner packaging is a plastic bag, suitable for long-distance transportation.

Application Performance

CCEWOOL soluble fiber tape has high-temp resistance, low thermal conductivity, thermal shock resistance, low heat capacity, excellent high-temp insulation performance, and a long service life.

CCEWOOL soluble fiber tape can resist the corrosion of non-ferrous metals, such as aluminum and zinc; it has good low-temp and high-temp strengths.

CCEWOOL soluble fiber tape is non-toxic, harmless, and has no adverse effects on the environment.

In view of the above advantages, the applications of CCEWOOL soluble fiber tape include:

Thermal insulation on various furnaces, high-temp pipelines, and containers.

Furnace doors, valves, flange seals, materials of fire doors, fire shutter, or high-temp furnace door's sensitive curtains.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com

Thermal insulation for engines and instruments, covering materials for fireproof cables, and high-temp fireproof materials.

Cloth for thermal insulation covering or high-temp expansion joint filler, and flue lining

High-temp resistant labor protection products, fire protection clothing, high-temp filtration, sound absorption and other applications in replacement of asbestos.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceramicfiber.com

www.cerockwool.com