

CCEFIRE® Refractory Mortar

Description:

CCEFIRE® Refractory mortar is a high temperature, air-setting mortar used as an adhesive to securely bind refractory material, which can be used into binding refractory brick, insulating brick and ceramic fibers. There are two types: dry powder mortar, which is mix the powder and additive and pack them with plastic woven bags. After soaked and stirred evenly, it can be put into use; other type is liquid status, which can be directly used without other process.

Technical data and Size:

CCEFIRE® Refractory Mortar	
Item	Index
Al₂O₃ %	≥42
Fe₂O₃ %	≤2.0
Max temperature	1300℃
Bonding time	1-3min
Bonding strength	110℃*24h ≥5MPa 1100℃ after-burning ≥7MPa
Modulus of Rupture	≥6MPa

Raw Materials

CCEFIRE refractory mortar is mainly made of high-quality refractory powder, high-strength and temperature-resistant chemical binders and additives,

Zibo Double Egret Thermal Insulation Co.,Ltd
Add: No.105 Liuquan Rd Zibo Shandong
Tel: +86-533-7986860
Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com
Website: www.ceramicfibres.com
www.ccceramicfiber.com
www.cerockwool.com

suitable for furnace masonry requiring small ash joints, good sealing, and high bonding strength.

Production Process

1. Excellent performance, ideal plasticity, and water retention
2. Very small shrinkage during drying and baking
3. High refractoriness
4. High bonding strength
5. Good resistance to chemical corrosion
6. Stable chemical properties

Quality Control

Each shipment has a dedicated quality inspector, and a test report is provided prior to the departure of products from the factory to ensure the export quality of each shipment of CCEFIRE.

A third-party inspection (such as SGS, BV, etc.) is accepted.

Production is strictly in accordance with ASTM quality management system certification.

The outer packaging of each carton is made of five layers of kraft paper, and outer packaging + pallet,, suitable for long-distance transportation.

Application Performance

1. CCEFIRE refractory mortar is used for masonry insulation bricks, special heavy bricks, and high aluminum heavy bricks.
2. CCEFIRE refractory mortar is used to prevent the intrusion of air and hot air into the masonry.
3. CCEFIRE refractory mortar is used to prevent the erosion of brick joints by molten slag and molten metals.

Zibo Double Egret Thermal Insulation Co.,Ltd

Add: No.105 Liuquan Rd Zibo Shandong

Tel: +86-533-7986860

Fax: +86-533-6077229

Email: ceramicfibres@ccewool.com

Website: www.ceramicfibres.com

www.ceceramicfiber.com

www.cerockwool.com